



---

FIBERGLASS COMPOSITE PIPE DIVISION  
1004 Ameron Road.  
Burkburnett Texas, 76354

May 9, 2009

Hector P. Mercado  
Engineering Manager  
940-569-8607  
Fax: 940-569-8644  
[hmercado@ameronfpd.com](mailto:hmercado@ameronfpd.com)

Ref: Fuel Compatibility of Dualoy® 3000/L & 3000/LCX

Ameron's Dualoy® 3000/L & 3000/LCX piping systems have been tested and were found to comply with the applicable requirements of UL971, Standard for Nonmetallic Underground Piping for Flammable Liquids with revisions through and including March 2, 2006. These include:

Diameters 2", 3", 4" & 6" Series Dualoy 3000/L Primary Carrier and Secondary Containment Piping, Diameters 2", 3" & 4" Series Dualoy 3000/LCX Integral Primary/Secondary Piping and Series PSX-20 and PSX-34 adhesives for conveying Primary Product, Vent and Vapor Recovery of Motor Vehicle Fuels, Concentrated Fuels, High Blend Fuels and Aviation and Marine Fuels.

Based on all available testing Ameron finds the following additional fuels suitable for use with the Dualoy® 3000/L and 3000/LCX piping systems: B2, B5, B20, B100, E10, E85, E100, low/medium/high grades of unleaded, aviation and marine fuels.

The primary pipe for the Series Dualoy® 3000/L system has maintained the same design performance since 1988.

Sincerely,

A handwritten signature in blue ink that reads 'Hector Mercado'. The signature is fluid and cursive, with the first and last names clearly legible.

Hector Mercado  
Engineering Manager